

TRUCKSTER XD



CLASS-LEADING POWER AND PRODUCTIVITY.

The Truckster XD makes quick work of your hardest jobs with the industry's largest standard payload and your choice of Kubota gas or diesel engines. A highly versatile bed - manufactured with strong heavy gauge steel, integrated stake pockets and tie-downs - makes effortless hauling for your heaviest loads. Built to operate in the toughest of conditions with the industry's highest approach angle, and largest ergonomic operator platform, your crew can count on the Truckster XD to handle the strenuous tasks with ease.

32.5 HP

OR

24.8 HP DIESEL ENGINE

23.6 CU FT BED VOLUME

3,550 LB

LET'S WORK.®



CUSHMAN° TRUCKSTER XD





OPTIONS & ACCESSORIES

- 66" box
- 2" receiver hitch
- Canopy (two or four post ROPS)
- Four-post ROPS Premium suspension seat (operator and passenger)
- Hi/Lo hydraulics with remote ports
- Hydraulic PTO
- Throttle control
- Turn signals
- Cab
- Doors
- Auto tailgate
- Heater

- · Fifth-wheel ball hitch including electric brake controller
- Core Harvester
- Top Dresser
- 1500 Vicon Spreader
- Quick Aerator
- Implement Lift
- Mirrors left and right
- · Windshield for four-post ROPS Storage accessory
- Work Light kit
- Backup alarm
- Exhaust spark arrestor
- Fifth-gear lock out

	GAS	DIESEL
BODY & CHASSIS		The second second
FRAME	Powder Coated Steel	
BODY & FINISH	Injection Molded	
STANDARD COLOR	Orange	
DIMENSIONS		
OVERALL LENGTH	132 in. w/o bed, 136 w/ bed	133 in. w/o bed, 136 w/ bed
OVERALL WIDTH	65 in	
OVERALL HEIGHT	78 in	
WHEEL BASE	65 in	
FRONT WHEEL TRACK	49 in	
REAR WHEEL TRACK	52 in	
GROUND CLEARANCE	6.5 in	
CARGO BOX CAPACITY	23.6 cu ft	
POWER		
POWER SOURCE	32.5 HP Kubota Gas Engine	24.8 HP Kubota Diesel Engine
VALVE TRAIN	3-Cylinder, 4-Cycle Liquid Cooled EFI	3-Cylinder, 4-Cycle Liquid Cooled
HORSEPOWER	32.5 HP	24.8 HP
BATTERY (QTY/TYPE)	12 Volt Battery	
KEY OR PEDAL START	Key Start	
COOLING SYSTEM	Liquid Cooled	
FUEL CAPACITY	7.0 gal. unleaded	7.0 gal. diesel
DRIVE TRAIN	Engine Shaft Direct Drive	
GEAR SELECTION	Five Speed Manual	
REAR AXLE RATIO	High 14.2:1 / Low 45:1	
PERFORMANCE		
SEATING CAPACITY	2-Person	
VEHICLE LOAD CAPACITY	3,550 LBS	
SPEED	23 mph	21 mph
TOWING CAPACITY	2,200 lbs, 3,500 w/ trailer brakes	
STEERING & SUSPE	ENSION	
STEERING	Hydrostatic Power	
FRONT/REAR SUSPENSION	Solid axle w/ leaf springs & shock absorbers	
SERVICE BRAKE	Heavy-Duty Hydraulic Four Wheel Disk Brakes w/ 10.7 in. Disk	
PARKING BRAKE	Hand Lever Actuated Disk Brakes on Rear Wheels	
FRONT TIRES	23 x 10.5 - 14 6-ply Ribbed (2WD) / 14 6-ply Treaded (4WD)	
REAR TIRES	26 x 12 - 14 6-ply Ultra Chevron Tread	

