

FACE NEW ROADS.

Transporting passengers just got easier with the all-new street legal Cushman Tour LSV, offered exclusively with an ELITE Lithium drivetrain powered by Samsung SDI technology. The backup camera, side and rearview mirrors, lap belts and additional safety features provide riders with the security and comfort of being certified to the highest LSV standard. Go further in comfort, style, and accessibility with the Tour LSV.

STREET LEGAL

FMVSS 500 & SAE J2358 CERTIFIED

FOUR FORWARD-FACING

SEATS


25 MPH

MAX SPEED

ZERO Maintenance

ELITE LITHIUM BATTERY







ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- 6.2 Triple Pack Battery Option for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake

STANDARD FEATURES

- Backup Camera
- Rear View Mirror with Integrated Display
- Pedestrian Warning System
- Maximum Speed of 25 MPH
- Lap Belts
- 4 Wheel Hydraulic Brakes
- Center High Mount Brake Light
- Large Fender Flares
- OPS (Operator Protective Structure) Rated Canopy Structure
- Side View Mirrors
- Turn Signals and Horn
- Stylish Dash with Versatile Storage Areas
- LED Headlights
- Brake Lights
- Limited Slip Differential
- Automatic Park Brake
- VIN number

OPTIONS & ACCESSORIES

- USB Ports
- Premium Steering Wheel
- Brush Guard
- Lighted License Plate Kit
- Lockable Trunk
- Cargo Basket
- Reflective Safety Triangle

CUSHMAN.COM



TOUR LSV / ELITE

STREET LEGAL

BODY & CHASSIS

| FRAME | Welded Steel with DuraShield™ Powder Coat |
|-----------------------|---|
| FRONT BODY AND FINISH | Injection Molded TPO |
| REAR BODY AND FINISH | Thermoform ABS |
| OPTIONAL BODY COLORS | Black, Bright White, Flame Red, Metallic Charcoal, Ocean Grey, Patriot Blue, Slate |
| STANDARD SEAT COLORS | Black, Grey, Oyster, Stone Beige |
| PREMIUM SEAT COLORS | Black, Mushroom, Grey |
| | |

DIMENSIONS

| 106.5 in (271 cm) | |
|-------------------|--|
| 46 in (117 cm) | |
| 75.5 in (192 cm) | |
| 77.5 in (197 cm) | |
| 38 in (97 cm) | |
| 39 in (99 cm) | |
| 7 in (18 cm) | |
| | 46 in (117 cm) 75.5 in (192 cm) 77.5 in (197 cm) 38 in (97 cm) 39 in (99 cm) |

POWER

| POWER SOURCE | 56.7V DC |
|--------------------|--|
| MOTOR TYPE | AC Induction |
| HORSEPOWER (KW) | 11.7 hp (8.7 kW) |
| ELECTRICAL SYSTEM | 56.7V |
| BATTERIES (TYPE) | Twin Pack |
| KEY OR PEDAL START | Pedal |
| BATTERY CHARGER | World Charger |
| SPEED CONTROLLER | 235 Amp AC Controller |
| DRIVETRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Limited Slip Differential with Helical Gears |
| GEAR SELECTION | Dash Mounted FNR/Key Switch |
| REAR AXLE RATIO | 16.99:1 (Forward) |

PERFORMANCE

| SEATING CAPACITY | 4-Person | |
|----------------------------|--------------------------|--|
| DRY WEIGHT | 966 lb (437 kg) | |
| CURB WEIGHT | 1040 lb (471 kg) | |
| DASH / IP STORAGE CAPACITY | 1123 sq in (18403 sq cm) | |
| VEHICLE LOAD CAPACITY | 800 lb (363 kg) | |
| TURNING RADIUS | 12.85 ft (3.92 m) | |
| OUTSIDE CLEARANCE CIRCLE | 23.9 ft (7.3 m) | |
| SPEED (LEVEL GROUND) | 25 mph (40.2 kph) | |
| TOWING CAPACITY | 500 lb (227 kg) | |

STEERING & SUSPENSION

| STEERING | Self-Compensating Rack and Pinion |
|---------------|--|
| SUSPENSION | Leaf Springs with Hydraulic Shock Absorbers |
| BRAKES | Four-Wheel Hydraulic, Front Disk; Rear Self-Adjusting Drum |
| PARKING BRAKE | Automatic Electromagnetic |

