

ONWARD 6 PASSENGER

Club Car®

THE CONFIDENT CHOICE

Why Club Car:

- **Engineered for longevity** with purpose-built components designed to outlast daily wear
- **Rust-proof aluminum chassis** that resists corrosion and stands up to heat, moisture, and time
- **Proven performance heritage**, refined through millions of rounds and rides worldwide
- **Manufactured in Augusta, Georgia**, backed by decades of craftsmanship and quality control

TRUE WARRANTY COVERAGE!

Parts AND Labor Coverage unlike some import brands with no labor coverage and poor replacement parts availability!



Available
Powertrains



STANDARD MODELS

NON-LIFTED



Glacier White



Midnight Silver

LIFTED



Glacier White



Midnight Silver

PREMIUM MODEL



Metallic Black



Metallic Black

STANDARD EQUIPMENT ON ALL MODELS

- Premium Seats
- Canopy and Premium Clear Windshield
- Comfort Grip Premium Steering Wheel
- Lockable Upper Dash Glove Box
- Wired Strut (soundbar-ready for easy upgrade)
- Lockable Side Glove Box Compartments
- Li-Ion models include Digital Display
- Li-Ion models include Dual Wireless Chargers

PREMIUM MODELS INCLUDE

Exclusive Color!

ALL Standard Equipment PLUS:

- Premium Soundbar
- Premium Wheel & Tire
- **NEW!** Premium Floormat
- **NEW!** Dash Pocket Lights
- Dual Wireless Chargers





	6 PASSENGER ONWARD PTV					
	GAS		HP ELECTRIC		XR LITHIUM	
DIMENSIONS	Non-Lifted	Lifted	Non-Lifted	Lifted	Non-Lifted	Lifted
Overall Length	143 inches	148 inches	143 inches	148 inches	143 inches	148 inches
Overall Width	48.8 inches	51.3 inches	48.8 inches	51.3 inches	48.8 inches	51.3 inches
Topped Height	75 inches	82 inches	75 inches	82 inches	75 inches	82 inches
Untopped Height	47.5 inches	54.5 inches	47.5 inches	54.5 inches	47.5 inches	54.5 inches
Wheelbase	102 inches	103 inches	102 inches	103 inches	102 inches	103 inches
Front Wheel Track	37 inches	40 inches	37 inches	40 inches	37 inches	40 inches
Rear Wheel Track	40 inches					
Ground Clearance	4.5 inches	6.4 inches	4.5 inches	6.4 inches	4.5 inches	6.4 inches
POWER						
Power Source	429 cc Kohler, Overhead Valve (OHV) with EFI		375 Amp AC Motor Controller			
Horsepower	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940		4.7 hp (3.5 kW) rated			
Fuel Capacity	5.6 gal (21.2 L)		N/A		N/A	
Batteries	12-volt (1)		Trojan T875 Flooded-Lead Acid		7.0 kWh	
Battery Charger	N/A		E.R.I.C, Automatic, 48-volt; UL, CSA listed		650W AC Delta Q	
Key or Pedal Start	Pedal					
Drivetrain	Motor Shaft Direct Drive					
Gear Selection	Dash Mounted FNR					
Rear Axle Ratio	14.85:1					
PERFORMANCE						
Seating Capacity	6					
Curb Weight	980 lb	1101 lb	1293 lb	1429 lb	1005 lb	1141 lb
Vehicle Load Capacity	1200 lb					
Turning Radius	151 inches	172 inches	151 inches	172 inches	151 inches	172 inches
High Speed (Level Ground)	19 mph (30 kph)					
STEERING & SUSPENSION						
Steering	SportDrive™ — Self-compensating double reduction helical rack & pinion					
Suspension (Front & Rear)	Independent leaf spring w/dual hydraulic shocks					
Brakes	Self-adjusting, rear-wheel mechanical drum					
Parking Brake	Foot actuated, 3-position					
BODY & CHASSIS						
Frame	AlumiCore™ — Ladder-style aluminum box beam					
Body and Finish	Automotive grade paint and UV protected molding					